

## M-BUS/MODBUS - M-BUS/C-BUS PROTOCOL CONVERTER

### CMC 422

#### APPLICATION

- M-Bus/ModBus or M-Bus/C-Bus protocol converter for acquiring thermal energy meter data.
- In 4 DIN rail module enclosure.
- Power supply 12...24 VAC/VDC

**Download driver to update software CMC 42x** (only with the login)

**Download software CMC 42x** (only with the login)

#### Revision History

#### Features

#### Technical data

- Hardware
  - No. Description
  - 1 RS-485 port
  - 1 C-Bus port
  - 1 M-Bus port
  - 2 DIP switches on front panel for device configuration
  - 2 Digital outputs
  - 3 Signalling LED
- Mechanics
  - Operating temperature 0...+60 °C
  - Storage temperature -10...+80 °C
  - Weight 185 g
  - Size 4 DIN modules
  - 90 x 105 x 71 mm (h x w x d)
- Electrical
  - Power supply: 230 Vac
  - Power consumption: 3VA
  - Output power supply 1 (+3.3 VAUX)+3.3 VDC
  - Output power supply 2 (+5 VAUX)+5 VDC
  - Maximum total output load on +5 VAUX and +3.3VAUX 100 mA
  - Power consumption at maximum load: 3.5VA
  - Front protection rating: IP 20
  - Rear protection rating: IP 20

Code	Description	Data Sheet
<b>CMC 422</b>	M-BUS/MODBUS - M-BUS/C-BUS protocol converter.	-