

WIRELESS SENSOR RECEIVER

CSW 868

APPLICATION

- The sensor receiver CSW 868 is used to create a wireless connection between a master and one or more wireless sensors (up to 40).
- It ensures two-way communication with the wireless sensors.
- Resources are managed flexibly and smartly to exploit the potential of each control instrument.

Features

Technical data

Hardware

- No. DESCRIPTION
- 1 Housing for 1 module for use with DIN rail
- 1 12 V DC power supply
- 1 RS485 serial port for connection to the master
- 1 SMA antenna connector
- Updatable firmware

Mechanical

- Operating temperature range: 0 – 45 (°C)
- Storage temperature range: -25 – +60 (°C)
- Ambient humidity class: F DIN 40040
- Module housing class: DIN 43700
- Housing material: NORYL SE1 GFN2 black plastic
- Dimensions: 17.5 x 90 x 62 (mm)
- Weight: 55 (g)

Electrical

- Power: 12 V DC (V)
- Apparent power: 5 (VA)
- Front panel degree of protection: IP 20
- Back panel degree of protection: IP 20
- Radio interference: VDE 0875/0871
- Construction standard: CEI

Code	Description	Data Sheet
CSW 868	Wireless sensor receiver.	–

SONDE E ACCESSORI

Code	Description	Data Sheet
------	-------------	------------