

## SELECTIVE MICROPROCESSOR-BASED DOMESTIC GAS DETECTORS WITH RELAY OUTPUT

### RGS 128 -228

#### APPLICATION

- Electronic digital detectors fitted with internal methane or LPG internal sensing element. Option of connecting 1 or 2 methane, LPG or CO outside sensors. Signals pre-alarm, alarm and fault in sensing element.
- Complies with CEI EN 50194 and CEI EN 50244 regulations.
- Optional sensors: 1 or 2 methane detecting sensors (SRS 158), LPG (SRS 258), CO (SRS 358).

#### Features

#### TECHNICAL DATA

- Power supply: 230 V~; Consumption: 2 VA;
- Domestic-type enclosure 130 x 80 x 37 mm; Protection: IP 20; Wall-mounting.
- Voltage-free SPDT relay output, rating max. 250 V~, 5 (1) A.

Code	Internal sensor	Alarm threshold	Pre-alarm threshold	Data Sheet
RGS 128	Methane	0,80%	0,50%	-
RGS 228	LPG	0,35%	0,20%	-

#### SONDE E ACCESSORI

Code	Description
SRS 158	Sensore civile per gas metano
SRS 258	Sensore civile per gas propano gpl
SRS 358	Sensore selettivo monossido di carbonio