

## RESET SHUT OFF N.O. GAS SOLENOID VALVES

### GAR ...

#### APPLICATION

- Used in conjunction with safety systems, for gas feed pipe shutoff
- The valves can only be opened manually, stay open only when powered is cut, and only close when powered up.

#### Features

#### TECHNICAL DATA

- Power supply 230 V~, 24 V~, 12 V-
- Voltage tolerance – 15%...+10%
- Power absorbed in Watts vedi tabella (3)
- Max. operating power vedi tabella (3)
- Protection IP 65 (gruppo 2)

Code	DN	Power supply		P.max <sup>(1)</sup> mbar	Flow rate m <sup>3</sup> /h <sup>(2)</sup>		Data Sheet
		V	W		0.5 mbar	1 mbar	
	SREWED						
<b>GAR 832</b>	1" 1/4	230 V AC	23	500	20	29	G 933
<b>GAR 432</b>	1" 1/4	24 V AC	22	500	20	29	G 933
<b>GAR 232</b>	1" 1/4	12 V DC	20	500	20	29	G 933
<b>GAR 840</b>	1" 1/2	230 V AC	23	500	20	29	G 933
<b>GAR 440</b>	1" 1/2	24 V AC	22	500	20	29	G 933
<b>GAR 240</b>	1" 1/2	12 V DC	20	500	20	29	G 933
<b>GAR 850</b>	2"	230 V AC	23	500	25	37	G 933
<b>GAR 450</b>	2"	24 V AC	22	500	25	37	G 933
<b>GAR 250</b>	2"	12 V DC	20	500	25	37	G 933
	SREWED						
<b>GAR 865</b>	65	230 V AC	23	500	63	92	G 933
<b>GAR 465</b>	65	24 V AC	22	500	63	92	G 933
<b>GAR 265</b>	65	12 V DC	20	500	63	92	G 933
<b>GAR 880</b>	80	230 V AC	23	500	76	115	G 933
<b>GAR 480</b>	80	24 V AC	22	500	76	115	G 933
<b>GAR 280</b>	80	12 V DC	20	500	76	115	G 933
<b>GAR 8100</b>	100	230 V AC	23	500	92	140	G 933
<b>GAR 4100</b>	100	24 V AC	22	500	92	140	G 933
<b>GAR 2100</b>	100	12 V DC	20	500	92	140	G 933
<b>GAR 8125</b>	125	230 V AC	23	500	275	400	G 933
<b>GAR 4125</b>	125	24 V AC	22	500	275	400	G 933
<b>GAR 2125</b>	125	12 V DC	20	500	275	400	G 933
<b>GAR 8150</b>	150	230 V AC	23	500	275	400	G 933
<b>GAR 4150</b>	150	24 V AC	22	500	275	400	G 933
<b>GAR 2150</b>	150	12 V DC	20	500	275	400	G 933
<b>GAR 8200</b>	200	230 V AC	57	500	360	525	G 933
<b>GAR 4200</b>	200	24 V AC	45	500	360	525	G 933
<b>GAR 2200</b>	200	12 V DC	40	500	360	525	G 933
<b>GAR 8300</b>	300	230 V AC	57	500	790	1200	G 933
<b>GAR 4300</b>	300	24 V AC	45	500	790	1200	G 933
<b>GAR 2300</b>	300	12 V DC	40	500	790	1200	G 933

(1) – Pressione massima di esercizio

(2) – Portate di gas metano con perdite di carico di 0,5 mbar (5mmCA) e 1 mbar (10 mmCA)

100 mbar = 10 kPa = 1.000 mmCA