

(1) – Maximum working pressure.

(2) – Flow of methane with pressure drop of 0.5 mbar (5mmWG) and 1 mbar (10 mmWG).

100 mbar = 10 kPa = 1.000 mm.WG

## N.O. GAS SOLENOID VALVES WITH MANUAL RE-SET

### GCRO ...

#### APPLICATION

- Without power they are closed; they have to be re-opened manually and remain open when powered.
- Approved Class A Group 2.

#### Features

#### TECHNICAL DATA

- Linkage : screwed female EN 10226
- Protection : IP 65
- Working temperature :- 15...+ 60°C

Code	DN	Power supply		P.max(1) mbar	Flow rate m <sup>3</sup> /h(2)		Data Sheet
		V	W		0.5 mbar	1 mbar	
<b>GCRO 815</b>	1/2"	230 V AC	9	500	1,8	2,8	G 924
<b>GCRO 415</b>	1/2"	24 V AC	8	500	1,8	2,6	G 924
<b>GCRO 215</b>	1/2"	12 V DC	8	500	1,8	2,6	G 924
<b>GCRO 820</b>	3/4"	230 V AC	9	500	3	4,5	G 924
<b>GCRO 420</b>	3/4"	24 V AC	8	500	3	4,5	G 924
<b>GCRO 220</b>	3/4"	12 V DC	8	500	3	4,5	G 924
<b>GCRO 825</b>	1"	230 V AC	9	500	4,5	4,5	G 924
<b>GCRO 425</b>	1"	24 V AC	8	500	4,5	4,5	G 924
<b>GCRO 225</b>	1"	12 V DC	8	500	4,5	4,5	G 924

(1) – Maximum working pressure.

(2) – Flow of methane with pressure drop of 0.5 mbar (5mmWG) and 1 mbar (10 mmWG).

100 mbar = 10 kPa = 1.000 mm.WG