


## 2-PORT ZONE BALL VALVES PN 10 (5...90 °C)

### HGM 2..

#### APPLICATION

Rotary ball valves for shut-off in zoned installations.  
Suitable for mounting on modular manifolds.



#### Features

- Body and ball in chromed brass; supplied with male connections for flat unions.

Code	DN body	Kvs <sup>(1)</sup> m <sup>3</sup> /h		female	Suitable actuator CDK 06. SVK 014/C		Data Sheet
		thr-port	by-pass		bar <sup>(2)</sup>	sec <sup>(3)</sup>	
<b>HGM 210</b>	Threaded 3/8"	m <sup>3</sup> /h 5,4	m <sup>3</sup> /h –	3/8"	6	60	M 812
<b>HGM 215</b>	1/2"	6	–	1/2"	6	60	M 812
<b>HGM 220</b>	3/4"	11	–	3/4"	6	60	M 812
<b>HGM 225</b>	1"	25,7	–	1"	6	60	M 812

(1) : Kvs - Flow coefficient: Flow in m<sup>3</sup>/h with valve open and pressure drop of.  
100 kPa = 10 mCA = 1 bar

(2) : bar - Maximum pressure differential  $\Delta p$  max. permitted by actuator.

(3) : sec - Time (seconds) necessary for actuator to make the whole valve run.